

ELP™-D



Labels for Life.



Thermal Transfer Printer

Identco's ELP™ D thermal transfer printer provides excellent print quality at a low cost, saving money without sacrificing performance. This printer prints 300 dpi at 5 inches per second, getting the job done fast. The ELP D printer is an excellent choice for printing all of our IMS Series formatted heat shrink, self lam labels, labels and cable marking tags.

**Available to quote today!
+1 (800) 533-2559**

Highlights

- ZPL emulation
- Center aligned media tracking
- External 8" OD media unwinder
- Uses ribbons coated side-out
- Small desktop footprint - saves space

Features

- 300 dpi thermal transfer printing
- Multiple connections (USB, serial, and Ethernet & wireless)
- Gap sensor
- Fully adjustable black mark sensor
- 2 year warranty
- On-site service plans
- Cutter or perf cutter



www.identco.com

ELP™ -D

Thermal Transfer Printer



Labels for Life.

LABEL PRINTER

Resolution	12 dots/mm (300 DPI)	
Printing method	Thermal Transfer & Direct Thermal	
Max. print speed	127 mm (5")/second	
Max. print width	106 mm (4.17")	
Max. print length	1,016 mm (40")	
Enclosure	Double-walled plastic	
Physical dimension	213 mm (W) x 188 mm (H) x 314 mm (D) 8.39" (W) x 7.40" (H) x 12.36" (D)	
Weight	2.8 kg (6.17 lbs)	
Label roll capacity	127 mm (5") OD Inside Printer • 203 mm (8") OD with External Media Stand	
Ribbon	300 m (984 ft), max OD 67mm, 1" core (ink coated side-out)	
Ribbon width	40 mm ~ 110 mm (1.6" ~ 4.3") 1" Cores	
Processor	32-bit RISC CPU	
Memory	<ul style="list-style-type: none"> • 4 MB Flash memory • 8 MB SDRAM • SD card reader for Flash memory expansion, up to 4 GB 	
Interface	<ul style="list-style-type: none"> • USB 2.0 • RS-232 • Centronics 	<ul style="list-style-type: none"> • Internal Ethernet, 10/100 Mbps (factory option) • Bluetooth (user option) • External 802.11 b/g/n wireless (user option)
Power	External universal switching power supply <ul style="list-style-type: none"> • Input: AC 100-240V, 2.5A, 50-60Hz • Output: DC 24V, 3.75A, 90W 	
Operation switch, button, LED	1 power switch, 1 feed button & 1 LED (3 colors: green, amber & red)	
Sensors	<ul style="list-style-type: none"> • Transmissive gap sensor • Ribbon end sensor • Head open sensor 	
Internal fonts	<ul style="list-style-type: none"> • 8 alpha-numeric bitmap fonts • Monotype Image® true type font engine with one CG Triumvirate Bold Condensed scalable font 	
Bar code	<ul style="list-style-type: none"> • 1D bar code Code 39, Code 93, Code 128UCC, Code 128 subset A, B, C, Codabar, Interleave 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2 (5) digits add-on, MSI, PLESSEY, POSTNET, RSS-Stacked, GS1 DataBar, Code 11 • 2D bar code PDF-417, Maxicode, DataMatrix, QR Code, Aztec 	
Font and barcode rotation	0, 90, 180, 270 degree	
Printer language	TSPL-EZ TM (Compatible to EPL, ZPL, ZPL II)	
Media type	Continuous & formatted shrink tube, die-cut, black mark, fan-fold, notched (outside wound)	
Media width	20 ~ 112 mm (0.78" ~ 4.4")	
Media thickness	0.06 ~ 0.19 mm (2.36 ~ 7.48 mil)	
Media core diameter	25.4 or 76.2 mm (1" or 3")	
Label length	10 ~ 1,016 mm (0.39" ~ 40")	
Environment condition	Operation: 5 ~ 40°C, 25 ~ 85% non-condensing Storage: -40 ~ 60°C, 10~ 90% non-condensing	
Safety regulation	FCC Class B, CE Class B, C-Tick Class B, UL, CUL, TÜV/Safety, CCC	
Environmental concern	Comply with RoHS, WEEE	
Accessories	<ul style="list-style-type: none"> • Windows labeling software CD disk • Quick start guide • USB cable • Power cord 	<ul style="list-style-type: none"> • External universal switching power supply • Label spindle fixing tab x 2, 1.5" core adapter x 2 • Ribbon spindle x 2 • Ribbon paper core
Limited warranty	<ul style="list-style-type: none"> • Printer: 2 years • Print head: 25 km (1 million inches) or 12 months which comes first • Platen: 50 km (2 million inches) or 12 months which comes first 	
Factory options	<ul style="list-style-type: none"> • Internal Ethernet interface (10/100 Mbps) • Real time clock 	
Dealer options	<ul style="list-style-type: none"> • Peel-off module • Guillotine cutter (full cut or partial cut) 	
User options	<ul style="list-style-type: none"> • Bluetooth module (serial interface) • 802.11 b/g/n wireless module (serial interface) • External roll mount, media OD, 214 mm (8.4") on a 1" or 3" core 	<ul style="list-style-type: none"> • 3" core label spindle • KP-200 Plus keyboard display unit • KU-007 Plus programmable smart keyboard
Printer Driver	<ul style="list-style-type: none"> • NiceLabel printer driver: TSC TTP-345 • Seagull printer driver: TT027-70 	

Note: All values shown are averages and should not be used for specification purposes. Test data and test results contained in this document are for general information only and shall not be relied upon by IDENTCO customers for designs and specifications, or be relied on as meeting specific performance criteria. Customers desiring to develop specifications or performance criteria for specific product applications should contact IDENTCO for further information. Revised 8/27/18.

UNITED STATES

HEADQUARTERS

28164 W. Concrete Drive
Ingleside, IL 60041
Phone: +1 (815) 385 - 0011
Fax +1 (815) 385 - 0359

MEXICO

MONTERREY

Carr. a Laredo Km. 16.5 Interior
14B, Col. Moisés Sáenz, 66613
Apodaca, Nuevo Leon
Phone: +52 (81) 8008 - 0438

GERMANY

FRANKFURT

Güterbahnhofstrasse 3-7
63450 Hanau
Phone: +49 (6181) 440 830 - 0
Fax: +49 (6181) 440 830 - 99

PRC

HONG KONG

Unit 1708, 17/F, 9 Wing Hong St.
Cheung Sha Wan, Kowloon
Phone: +852 2959 2156
Fax: +852 2959 2019

MALAYSIA

PENANG

Suite 163E, Level 16, Room 1602
Hunza Tower Gurney Paragon
Jalan Kelawai, Georgetown
10250 Penang
Phone: +6012 466 - 0866